

KW-BSE-02(硬木)

椅子(凳子)座面加载垫

Seat Loading Pad**Technical:**

Field of Application	BS EN 1335-3:2009 5.3 (Fig.1 or Figure A.2) Seat Loading Pad		坐具加载垫		
	BS EN 1335-3:2009 Figure A.1 Seat Loading Pad		坐具加载垫		
	EN 1725:1998 Fig A.1 Edge loading pad geometry: hardwood construction		(坐具)加载垫几何图: 硬木造样		
	EN 1728:2001 5.5 (Fig.4) Seat loading pad-Overall dimensions		(坐具)加载垫: 外廓尺寸		
	ENV 581-2:2000 Fig C.1 Seat loading pad geometry - Hardwood construction		坐具加载垫几何图: 硬木造样		
Structure Characteristics	1.Hardwood splicing,the size and material meet the standard requirement.				
	2.Simple 'plug' style connect. Easy assemble and disassemble.				
	3.Assemble the universal joint, 25 degree swing angle.				
Main Parts	Part Name	Function	Material	Surface Treatment	Color
	Plug Adapter	Join air cylinder	Spring	Harden	Black
	Adapter		Steel	Passivation	Black
	Universal joint	Fit to any change	Cast iron	Electrophoretic-coated	Blue
	"Hip"	Simulate the body	Hardwood	Paint	Wood primary
Installation and Transportation	Main Size	L490±15mm W 390±15mm H75±5			
	Weight	7.13 Kg			

**Kingwells**

东莞市锦辉试验设备制造厂

Kingwells Test Equipment Mfg., Ltd.

地址:广东省东莞市南城区白马方屋岔村1巷1号

电话: 86-769-22906718 传真: 86-769-22909619

Web: www.kingwells.com

E-Mail: info@kingwells.com