

VTR-100, 200, 500
 模拟运输振动台
 Vibration Tester

注册专利:
 ZL 2011 2 0344862.8
 ZL 2011 3 0305830.2

Structure characteristics:

- 1.Split removable control.
- 2.Optional time or control number control modes.
- 3.Digital display time system and digital display counter with stop / off memory function.
- 4.Digital display speed.
- 5.Use of AC frequency control
- 6.Aluminum frame rail, the operation is simple and convenient.
- 7.Table fireproofing board wear resistant impact resistance.
- 8.Manually handle screw mounted head sample.



Technical:

Field of Application	ISTA 1A/1B; ASTM D 999		
Model	VTR-100	VTR-300	VTR-500
Rated load	75 kg	150 kg	1000 Lbs
Size	1.1 x0.98m	1.3x1.2m	2.0x2.2m
Package Restraints	0.33m		0.6m
Work Time	0-999 hours, power failure memory, count down / timing, timing unit to select, output control		
Counter	1-999999 times, power failure memory, count down /count, output control		
Max Acceleration	1.25g		
Frequency Range	Frequency Adjustment from 2 to 5 Hz(120-320 C.P.M)		
Amplitude	25.4mm		
Standard Motions	AC frequency conversion motor		
Power	220 V60Hz	380V 20A	
Non Standard Accessories	Vibration Tester special peeler gauge		



Kingwells

东莞市锦辉试验设备制造厂
Kingwells Test Equipment Mfg., Ltd.
 地址: 广东省东莞市南城区白马方屋坵村1巷1号
 电话: 86-769-22906718 传真: 86-769-22909619
 Web: www.kingwells.com.cn
 E-Mail: info@kingwells.com.cn